



RRP-440.1/072
(not shown)
single connector
replacement cable.
Length: 72 inches.



Next-Gen™ EOT Battery Pack Chargers

**Fully Compatible Cost Effective Chargers for
EOT's with 24 VDC input for onboard charging.
Quantum/Siemens**

3920 Smart Charging only.

Wabtec

EOT-ATX-NG

EOT-ATX-NG3 and NG3T

EOT-ATX-G4

Charger Features

- **Battery Polarity Reversal:** Protects the charger and battery pack against incorrectly installed batteries.
- **Over Current Protection:** Protects the charger from over-current demand.
- **Short Circuit Protection:** Protects the charger from short-circuit damage.
- **Over Voltage Protection:** Protects the battery pack from damage.

RRP-441Single port Next-Gen™ Charger.

RRP-442Dual port Next-Gen™ Charger.

RRP-444Four port Next-Gen™ Charger.

RRP-446Six port Next-Gen™ Charger

RRP-448Eight port Next-Gen™ Charger

*RRP-433A single SmartPak, RediPak, Quantum port
plus a single NextGen battery port.*

Charger Specifications

Input Voltage: 100-120VAC

Input Frequency: 47-63Hz

Output Voltage: 24 VDC

Output Current: DC 5,000mA

Battery Capacity: 5-20Ahr (recommended)

Operating Temp: +32F/0C to +104F/40C

Storage Temp: -4F/-20C to +140F/60C

**Distributed
By**

PRIMUS

www.primuselectronics.com

sales@primuselectronics.com

Tel: 888-303-7245 Fax: 800-767-7605

Key Contact

Pat Morgan: pmorgan@primuselectronics.com